




NEW! CSC SERIES COMPOSITE SAFES


AMSEC CSC SERIES COMPOSITE SAFES are an affordable solution when you want to protect both documents from fire and valuables from burglary attacks. During extreme testing procedures the CSC SERIES COMPOSITE safes passed a 2-Hour, 350°F factory fire test certification.



Interior temperature less than 350°F for a period of 2 Hours at 1700°F



CSC4520



CSC3018



CSC1913

COMMERCIAL SECURITY SAFES

Features:

Door:

- Overall thickness of 4-5/8" and is constructed with a 2" defense barrier of outer and inner steel plates creating a burglary resistant structure enclosing a unique proprietary, fire resistant material.

Body:

- Total protective thickness of 2-7/8" enclosing a unique, high-density fire and burglary resistant composite material.
- Durable powder coated adjustable shelves.
- Removable casters provide easy delivery and installation.

Fire Endurance:

- 2 hour, 350°F factory fire rating. Tested at temperatures up to 1700°F.
- Heat expandable intumescent door seal guards contents against severe fires.

Locking Mechanism:

- Two to four 1½" diameter solid steel chrome-plated locking bolts.
- Two to three 1½" diameter solid steel dead bolts lock deep into body preventing door removal during a forced entry attempt.
- U.L. Listed Group II combination lock with chrome-plated spy-proof dial. Optional electronic locks available.
- Lock protected by a tempered glass reload device.
- Heavy duty steel hinges provide easy, smooth door operation.
- One internal counter-sunk anchor hole and mounting hardware are provided to securely anchor safe.
- Attractively accented with a full width fascia panel and matching three point handle.
- Durable and attractive light gray textured finish.



CSC1413

OPTIONAL STORAGE CABINETS AVAILABLE IN MODELS CSC3018 AND CSC4520. NO KIT NEEDED, DRAWERS SLIDE RIGHT IN. SEE PAGE 45 FOR MORE DETAILS



Model	Inside Dim H x W x D	Outside Dim H x W x D	Weight	Cubic In. Capacity	Bolts	Shelves	Rubber Feet or Casters
CSC1413	14 x 12.5 x 12.2	19.5 x 18 x 19.9	256	2,135	4	1	Rubber Feet
CSC1913	19 x 12.5 x 12.2	23.8 x 18 x 19.9	318	2,898	4	2	Rubber Feet
CSC3018	30 x 18 x 16.3	35.5 x 23.5 x 24	462	8,802	7	3	Casters
CSC4520	45 x 20 x 21.2	50.5 x 25.5 x 28.9	768	19,080	7	4	Casters

* Add 2" to outside depth for handle, dial and hinge projection.
* Add 4¼" (casters) and 1" (rubber feet) to outside height.