

# COMMERCIAL FIRE & SECURITY SAFES

AMERICAN SECURITY PRODUCTS COMPANY



**ALLIED  
SAFE & VAULT**  
[www.alliedsafe.com](http://www.alliedsafe.com)

The AMSEC CSC series composite safes are an affordable solution when you want to protect both documents from fire and valuables from burglary attacks. During extreme testing procedures the CSC series safes earned the U.L. (RSC) Residential Security Container burglary label and passed a 1-hour, 350°F factory fire test certification.

## Features:

### Door:

- Overall thickness of 4-5/8" and is constructed with a 2" defense barrier of outer and inner steel plates creating a single structure enclosing a unique, high-density fire and burglary resistant composite material.
- Defense barrier houses a proprietary amalgamation of nuggets and steel fibers to withstand concentrated attacks with the most sophisticated equipment used by burglars today.

### Body:

- Total protective thickness of 2-7/8" enclosing a high-density burglary and fire resistant composite material with nuggets and steel fibers.
- High strength adjustable shelves.

### Fire Endurance:

- One hour, 350°F factory fire rating. Tested at temperatures up to 1750°F.
- Fire gasket surrounding the entire door jamb.

### Locking Mechanism:

- Three massive 1-1/4" diameter solid steel chrome-plated locking bolts.

- Three solid steel dead bolts lock deep into body preventing door removal during a forced entry attempt.
- U.L. Listed Type 1 (ESL-10) chrome plated electronic lock standard. Optional Group II combination lock available.
- Lock protected by a spring-loaded auxiliary relock device.
- Heavy-duty 1/4" drill resistant carburized hard plate with drill shattering tungsten carbide insert.
- Heavy duty steel hinges provide easy smooth door operation.
- One internal counter-sunk anchor hole and mounting hardware are provided to securely anchor safe.
- Attractively accented with a full width fascia panel, matching three point handle, plush velour shelves, back cover and base.
- Durable and attractive parchment textured finish.



CSC1717



File No: BP6526



Interior temperature less than 350 F for a period of 1 hour at 1750 F.

Model No.	Inside H x W x D	Outside H x W x D*	Cubic Inch Capacity	Interior Shelves	Wt. Lbs.
CSC1717	17 x 17 x 17	22 <sup>3</sup> / <sub>4</sub> x 22 <sup>3</sup> / <sub>4</sub> x 24 <sup>3</sup> / <sub>4</sub>	4,913	1	655
CSC2517	25 x 17 x 17	30 <sup>3</sup> / <sub>4</sub> x 22 <sup>3</sup> / <sub>4</sub> x 24 <sup>3</sup> / <sub>4</sub>	7,225	2	800
CSC3417	34 x 17 x 17	39 <sup>3</sup> / <sub>4</sub> x 22 <sup>3</sup> / <sub>4</sub> x 24 <sup>3</sup> / <sub>4</sub>	9,826	2	980

\* Add 2" to outside depth for handle, dial and hinge projection.